

POURABLE SEALER S-10 PART A

1. Identification of the substance/preparation and of the company/undertaking

1.1 Identification of the substance or preparation:

Synonyms: none
 CAS No. : N.A.
 EC index No. : N.A. NFPA code : N.D.
 EINECS No. : N.A. Molecular weight : N.A.
 RTECS No. : N.A. Formula : N.A.

1.2 Use of the substance or the preparation:
 Construction: Sealing compound

1.3 Company/undertaking identification:

Firestone Building Products
 Ikaroslaan 75
 B-1930 Zaventem
 Tel. : +32 2 711 44 50
 Fax : +32 2 721 27 18
 Email: info@fbpe.be

1.4 Telephone number for emergency:

+32 70 245 245
 Poison Centre
 p/a Militair Hospitaal Koningin Astrid, Bruynstraat 1, B-1120 Brussel

2. Composition/information on ingredients

Hazardous ingredients	CAS No.	Conc. in %	Hazard symbol	Risks (R-phrases)
	EINECS/ELINCS No.			
calcium carbonate	471-34-1	30-45	-	-
	207-439-9			
silicon dioxide	7631-86-9	3-12	-	-
	231-545-4			

3. Hazards identification

- No hazard classification in accordance with directives 67/548/EEC and 1999/45/EC

4. First aid measures

4.1 Eye contact:

- Consult a doctor/medical service if irritation persists
 - Rinse immediately with water

4.2 Skin contact:

- Consult a doctor/medical service if irritation persists
 - Rinse with water
 - Soap may be used

4.3 After inhalation:

- Consult a doctor/medical service if breathing problems develop
 - Remove the victim into fresh air
 - Unconscious: maintain adequate airway and respiration

POURABLE SEALER S-10 PART A

4.4 After ingestion:

- Consult a doctor/medical service if you feel unwell
- Never give water to an unconscious person
- Do not induce vomiting

5. Fire-fighting measures

5.1 Suitable extinguishing media:

- Water spray
- Polyvalent foam
- BC powder
- Carbon dioxide

5.2 Unsuitable extinguishing media:

- No data available

5.3 Special exposure hazards:

- Combustible
- On burning: release of toxic and corrosive gases/vapours (nitrous vapours, carbon monoxide - carbon dioxide)

5.4 Instructions:

- Dilute toxic gases with water spray

5.5 Special protective equipment for firefighters:

- Heat/fire exposure: compressed air/oxygen apparatus
- Protective clothing for exposure to chemicals

6. Accidental release measures

6.1 Personal protection/precautions:

See heading 8.2/8.3/13

6.2 Environmental precautions:

- Contain leaking substance

6.3 Methods for cleaning up:

- Take up liquid spill into a non combustible material e.g.: sand
- Scoop absorbed substance into closing containers
- Clean contaminated surfaces with an excess of water
- Wash clothing and equipment after handling

7. Handling and storage

7.1 Handling:

- Observe normal hygiene standards

7.2 Storage:

- Keep container tightly closed
- Store at room temperature
- Keep out of direct sunlight
- Store in a dry area
- Keep away from: heat sources, oxidizing agents, combustible materials, acids, bases, water/moisture

Storage temperature	: 15/25	°C
Quantity limits	: N.D.	kg
Storage life	: 365	days
Materials for packaging	:	
- suitable	: no data available	
- to avoid	: no data available	

7.3 Specific uses:

- See information supplied by the manufacturer

POURABLE SEALER S-10 PART A

8. Exposure controls/Personal protection

8.1 Exposure limit values:

calcium carbonate

TLV-TWA	: (10)	mg/m ³		ppm
TLV-STEL	: -	mg/m ³		ppm
OES-LTEL	: 4 R/10 I	mg/m ³	-	ppm
OES-STEL	: -	mg/m ³	-	ppm
MAK	:	mg/m ³		ppm
MAC-TGG 8 h	:	mg/m ³		
MAC-TGG 15 min.	:	mg/m ³		
VME-8 h	: 10	mg/m ³	-	ppm
VLE-15 min.	: -	mg/m ³	-	ppm
GWBB-8 h	: 10	mg/m ³	-	ppm
GWK-15 min.	: -	mg/m ³	-	ppm
EC	:	mg/m ³		ppm
EC-STEL	:	mg/m ³		ppm

silicon dioxide

TLV-TWA	: (0.1 R/10 I)	mg/m ³		ppm
TLV-STEL	: (-)	mg/m ³		ppm
OES-LTEL	: 2.4 R/6 I	mg/m ³	-	ppm
OES-STEL	: -	mg/m ³	-	ppm
MAK	: 0.3 A/4 E	mg/m ³		ppm
MAC-TGG 8 h	:	mg/m ³		
MAC-TGG 15 min.	:	mg/m ³		
VME-8 h	:	mg/m ³		ppm
VLE-15 min.	:	mg/m ³		ppm
GWBB-8 h	: 0.1R/2 rook/10 I	mg/m ³	mg/m ³	- ppm
GWK-15 min.	: -	mg/m ³	-	ppm
EC	:	mg/m ³		ppm
EC-STEL	:	mg/m ³		ppm

Sampling methods:

- Silica, Amorphous (Respirable) NIOSH 7501
- Silica, Amorphous OSHA CSI

8.2 Exposure controls:

8.2.1 Occupational exposure controls:

- Measure the concentration in the air regularly
- Work under local exhaust/ventilation

8.2.2 Environmental exposure controls: see heading 13

8.3 Personal protection:

8.3.1 respiratory protection:

- Respiratory protection not required in normal conditions

8.3.2 hand protection:

- Gloves
- Suitable materials: Rubber
- Breakthrough time: N.D.

POURABLE SEALER S-10 PART A

8.3.3 eye protection:

- Safety glasses

8.3.4 skin protection:

- Protective clothing

Suitable materials:

Rubber

9. Physical and chemical properties

9.1 General information:

Appearance (at 20°C) : Liquid
Odour : Mild
Colour : Light grey

9.2 Important health, safety and environmental information:

pH value : N.D.
Boiling point/boiling range : N.D. °C
Flashpoint : 185 °C
Explosion limits : N.D. vol% (°C)
Vapour pressure (at 20°C) : < 0.1 hPa
Vapour pressure (at 50°C) : N.D. hPa
Relative density (at 20°C) : 1.3
Water solubility : Poorly soluble
Soluble in : N.D.
Relative vapour density : > 2
Viscosity : N.D. Pa.s
Partition coefficient n-octanol/water : N.D.
Evaporation rate : N.D.
ratio to butyl acetate : N.D.
ratio to ether : N.D.

9.3 Other information:

Melting point/melting range : N.D. °C
Auto-ignition point : N.D. °C
Saturation concentration : N.D. g/m³

10. Stability and reactivity

10.1 Conditions to avoid/reactivity:

- Stable under normal conditions

10.2 Materials to avoid:

- Keep away from: heat sources, oxidizing agents, combustible materials, acids, bases, water/moisture

10.3 Hazardous decomposition products:

- On burning: release of toxic and corrosive gases/vapours (nitrous vapours, carbon monoxide - carbon dioxide)

POURABLE SEALER S-10 PART A

11. Toxicological information

11.1 Acute toxicity:

LD50 oral rat	: N.D.	mg/kg
LD50 dermal rat	: N.D.	mg/kg
LD50 dermal rabbit	: N.D.	mg/kg
LC50 inhalation rat	: N.D.	mg/l/4 h
LC50 inhalation rat	: N.D.	ppm/4 h

11.2 Chronic toxicity:

EC carc. cat. : not listed
EC muta. cat. : not listed
EC repr. cat. : not listed

Carcinogenicity (TLV) : not listed
Carcinogenicity (MAC) : not listed
Carcinogenicity (VME) : not listed
Carcinogenicity (GWBB) : not listed

Carcinogenicity (MAK) : not listed
Mutagenicity (MAK) : not listed
Teratogenicity (MAK) : C (silicon dioxide)

IARC classification : not listed

11.3 Routes of exposure: ingestion, inhalation, eyes and skin

11.4 Acute effects/symptoms:

- Unlikely to cause harmful effects

11.5 Chronic effects:

- Contains a substance of group C (MAK-Schwangerschaftsgruppe)(silicon dioxide)
- Not listed in carcinogenicity class (IARC,EC,TLV,MAK)
- Not listed in mutagenicity class (EC,MAK)

POURABLE SEALER S-10 PART A

12. Ecological information

12.1 Ecotoxicity:

- No data available

12.2 Mobility:

- Volatile organic compounds (VOC): N.D.%
- Poorly soluble in water
- Substance sinks in water

For other physicochemical properties see heading 9

12.3 Persistence and degradability:

- biodegradation BOD₅ : N.D. % ThOD
- water : - No data available
- soil : T ½: N.D. days

12.4 Bioaccumulative potential:

- log P_{ow} : N.D.
- BCF : N.D.

12.5 Other adverse effects:

- WGK : N.D.
- Effect on the ozone layer : Not dangerous for the ozone layer (1999/45/EC)
- Greenhouse effect : no data available
- Effect on waste water purification : no data available

13. Disposal considerations

13.1 Provisions relating to waste:

- Waste material code (75/442/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 08 04 10 (waste adhesives and sealants other than those mentioned in 08 04 09)

13.2 Disposal methods:

- Recycle/reuse
- Do not discharge into the sewer
- Do not discharge into surface water

13.3 Packaging/Container:

- No available data

POURABLE SEALER S-10 PART A

14. Transport information

- 14.1 Classification of the substance in compliance with UN Recommendations
- | | | |
|----------------------|---|-------------|
| UN number | : | - |
| CLASS | : | NOT SUBJECT |
| SUB RISKS | : | |
| PACKING | : | |
| PROPER SHIPPING NAME | : | |
- 14.2 ADR (transport by road)
- | | | |
|-----------------------|---|-------------|
| CLASS | : | NOT SUBJECT |
| PACKING | : | |
| CLASSIFICATION CODE | : | |
| DANGER LABEL TANKS | : | |
| DANGER LABEL PACKAGES | : | |
- 14.3 RID (transport by rail)
- | | | |
|-----------------------|---|-------------|
| CLASS | : | |
| PACKING | : | NOT SUBJECT |
| CLASSIFICATION CODE | : | |
| DANGER LABEL TANKS | : | |
| DANGER LABEL PACKAGES | : | |
- 14.4 ADNR (transport by inland waterways)
- | | | |
|-----------------------|---|-------------|
| CLASS | : | NOT SUBJECT |
| PACKING | : | |
| CLASSIFICATION CODE | : | |
| DANGER LABEL TANKS | : | |
| DANGER LABEL PACKAGES | : | |
- 14.5 IMDG (maritime transport)
- | | | |
|------------------|---|-------------|
| CLASS | : | NOT SUBJECT |
| SUB RISKS | : | |
| PACKING | : | |
| MFAG | : | |
| EMS | : | |
| MARINE POLLUTANT | : | |
- 14.6 ICAO (air transport)
- | | | |
|---|---|-------------|
| CLASS | : | NOT SUBJECT |
| SUB RISKS | : | |
| PACKING | : | |
| PACKING INSTRUCTIONS PASSENGER AIRCRAFT | : | |
| PACKING INSTRUCTIONS CARGO AIRCRAFT | : | |
- 14.7 Special precautions in connection with transport
- | | | |
|--|---|--|
| | : | not restricted for any mode of international transport |
|--|---|--|

15. Regulatory information

Classification according to directives 67/548/EEC and 1999/45/EC

NOT APPLICABLE

POURABLE SEALER S-10 PART A

16. Other information

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

N.A. = NOT APPLICABLE
N.D. = NOT DETERMINED
(*) = INTERNAL CLASSIFICATION (NFPA)

Exposure limits:

TLV : Threshold Limit Value - ACGIH USA
OES : Occupational Exposure Standards - United Kingdom
MEL : Maximum Exposure Limits - United Kingdom
MAK : Maximale Arbeitsplatzkonzentrationen - Germany
TRK : Technische Richtkonzentrationen - Germany
MAC : Maximale aanvaarde concentratie - The Netherlands
VME : Valeurs limites de Moyenne d'Exposition - France
VLE : Valeurs limites d'Exposition à court terme - France
GWBB : Grenswaarde beroepsmatige blootstelling - Belgium
GWK : Grenswaarde kortstondige blootstelling - Belgium
EC : Indicative occupational exposure limit values - directive 2000/39/EC

I : Inhalable fraction = **T**: Total dust = **E**: Einatembarer Aerosolanteil
R : Respirable fraction = **A**: Alveolengängiger Aerosolanteil/Alveolar dust
C : Ceiling limit

a:	aerosol	r:	rook/Rauch	(fume)
d:	damp (vapour)	st:	stof/Staub	(dust)
du:	dust	ve:	vezel	(fibre)
fa:	Faser (fibre)	va:	vapour	
fi:	fibre	om:	oil mist	
fu:	fume	on:	olienevel/Ölnebel	(oil mist)
p:	poussière (dust)	part:	particles	

Chronic toxicity:

K : List of the carcinogenic substances and processes - The Netherlands